

## DATASHEET

### IS-MC540.1

MULTI CHARGER  
FOR IS540.X



### PRODUCT DESCRIPTION

The Multi Charger IS-MC540.1 allows charging of up to five devices and its spare batteries at the same time. It is compatible with the devices IS540.1, IS540.M1 and IS540.2

- 1) Charging tray for single battery
- 2) Charging slot IS540.x
- 3) Indicator LED IS540.X: Display for charging status IS540.x
- 4) Indicator LED battery: Display for battery charging status

### TECHNICAL FEATURES

|                      |                                                            |
|----------------------|------------------------------------------------------------|
| <b>Input</b>         | 100-240 V   1,1 A   50-60 Hz                               |
| <b>Output</b>        | DC 5 V                                                     |
| <b>Dimensions</b>    | 593 x 112 x 90 mm (LxWxH)                                  |
| <b>Weight</b>        | ~ 1725 g                                                   |
| <b>Connection</b>    | Charging contacts                                          |
| <b>Capacity</b>      | Maximum 5 devices and its spare batteries at the same time |
| <b>Compatibility</b> | IS540.1, IS540.M1, IS540.2                                 |

### SET CONTENT

Multi Charger IS-MC530.1, Power Cable C7 AU/EU/UK/US, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.

# DATASHEET

## IS540.M1



### APPROVALS



ATEX approval: Mining  
 Ⓜ I M1 Ex ia I Ma  
 Ⓜ II 2G Ex ib IIC T4 Gb  
 Ⓜ II 2D Ex ib IIIC T1 35°C Db



IECEx approval: Mining  
 Ex ia I Ma  
 Ex ib IIC T4 Gb  
 Ex ib IIIC T1 35°C Db

### TECHNICAL FEATURES MODEL M540A01

|                                  |                                                                                                                                                                                                                                                             |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Operating system</b>          | Android™ 12                                                                                                                                                                                                                                                 |
| <b>Processor</b>                 | Qualcomm® QCM6490 Octa Core                                                                                                                                                                                                                                 |
| <b>Memory</b>                    | 8 GB RAM   128 GB internal memory   microSD memory up to 128 GB                                                                                                                                                                                             |
| <b>Supported frequency bands</b> | 2G GSM: 850/900/1800/1900 MHz<br>3G WCDMA: B1/2/4/5/8<br>4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/26/28/29/30/66/71<br>4G LTE-TDD: B38/39/40/41/42/43/48<br>5G NR: n1/n2/n3/n5/n7/n8/n12/n20/n25/n28/n30/n38/n40/n41/n48/n66/n71/n77/n78/n79 |
| <b>Dimensions</b>                | Size: 180,0 x 84,9 x 20,6 mm   weight: 422 g                                                                                                                                                                                                                |
| <b>Display</b>                   | 6"   Corning® Gorilla® Glass 3 <sup>rd</sup> generation   1080 x 2160 pixels   FHD                                                                                                                                                                          |
| <b>Battery</b>                   | 4400 mAh   replaceable                                                                                                                                                                                                                                      |
| <b>Camera</b>                    | 48 MP AF rear camera   5 MP FF front camera                                                                                                                                                                                                                 |
| <b>SIM support</b>               | 1 nano SIM + eSIM                                                                                                                                                                                                                                           |
| <b>Connections</b>               | Wi-Fi® 6: IEEE 802.11 a/b/g/n/ac/ax/e/k/r/v<br>Bluetooth® 5.2<br>GPS, A-GPS, Glonass, A-Glonass, Beidou, Galileo<br>Near Field Communication (NFC)                                                                                                          |
| <b>Ports in/out</b>              | 16-pin ISM interface<br>USB-C                                                                                                                                                                                                                               |
| <b>Sensors</b>                   | Accelerometer, Gyroscope, Light, Magnetic, Proximity, Pressure sensors                                                                                                                                                                                      |
| <b>Types of protection</b>       | IP68 dust-/waterproof   MIL-STD-810H   usable from -20 °C to +55 °C                                                                                                                                                                                         |

### FURTHER FEATURES

Red key top | Optional functions assignable via Button App (system integrated), e.g. LWP

Side key left | Optional functions assignable via Button App (system integrated), e.g. PTT

Amplified loudspeaker

### SET CONTENT

Smartphone, Battery, i.safe PROTECTOR 2.0 Type C USB Cable, Power Adapter universal, Screwdriver, Display Protection Foil, Display Cleaning Cloth, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.

## GROUP I M1 MINING



➤ Capture, analyze and document thermal images

◀ IS-TC1A.M1 ▶



The set consisting of the thermal imaging camera IS-TC1A.M1 and the industrial smartphone IS530.M1 detects temperatures in the Ex-hazardous area from -40 °C to 330 °C in a matter of seconds via the Seek Thermal app (free download in Google Play Store). The thermal images and videos are processed and documented directly via the ISM interface of the IS530.M1 smartphone.

# DATASHEET

## IS-TC1A.M1



### APPROVALS



ATEX approval: Ex-Zone M1 Mining  
⊕ I M1 Ex ia I Ma  
⊕ II 2G Ex ib IIC T4 Gb  
⊕ II 2D Ex ib IIIC T135°C Db



IECEx approval: Ex-Zone M1 Mining  
Ex ia I Ma  
Ex ib IIC T4 Gb  
Ex ib IIIC T135°C Db

### TECHNICAL FEATURES

|                             |                                                                             |
|-----------------------------|-----------------------------------------------------------------------------|
| <b>Sensor resolution</b>    | 200 (h) x 150 (v)   30000 Pixels   FixFocus   Digital zoom over app         |
| <b>Sensor sensitivity</b>   | 65 mK (typical)                                                             |
| <b>Frame rate</b>           | <9 Hz to 32 Hz                                                              |
| <b>Scene dynamic range</b>  | -40 °C to 330 °C                                                            |
| <b>Temperature accuracy</b> | ± 7 °C and 7 % (at 5 °C to 140 °C)   ± 10 °C and 10 % (at 140 °C to 330 °C) |
| <b>Detection range</b>      | up to 300 m                                                                 |
| <b>Recognition range</b>    | up to 75 m                                                                  |
| <b>Identification range</b> | up to 25 m                                                                  |
| <b>View range</b>           | 35° (HFOV)   26° (VFOV)                                                     |
| <b>Dimensions</b>           | size: 112 x 82 x 50 mm   weight: 190 g                                      |
| <b>Power supply</b>         | over the connected mobile device                                            |
| <b>Communication</b>        | over the multi functional ISM interface of the IS530.1                      |
| <b>Types of protection</b>  | IP68   MIL-STD 810H   useable from -20 °C to + 55 °C                        |

## IS530.M1



Android™ 13



4,5" Gorilla Glass®  
3. generation,  
resolution 854 x 480 pixels



3600 mAh battery,  
replaceable,  
3,8 V, 13,68 Wh



Bluetooth® 5



GSM 850/900/1800/1900 MHz  
WCDMA: UMTS B1/2/4/5/8  
LTE-FDD: B1/2/3/4/5/7/8/12  
with MFBI B13/14/17/20/25/  
26/28A/28B/29/30/66  
LTE-TDD: B38/B39/B40/B41  
TD-SCDMA: B34/B39



Qualcomm Snapdragon SDM660 Octa-Core  
Kryo Gold-Quad cores, 2,2 GHz  
Kryo Silver-Quad cores, 1,8 GHz  
4 GB RAM  
64 GB internal memory



2,4 GHz + 5 GHz: IEEE 802.11  
a/b/g/n/ac/e/k/r/h with hotspot  
for max. 8 connections

The complete description you will find on our homepage: [www.isafe-mobile.com](http://www.isafe-mobile.com)




Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.

## DATASHEET

# IS-HS2A.1

PTT/HEADSET  
Air Tube Earplug/Microphone



## EX-SPECIFICATIONS

The **IS-HS2A.1** is a headset suitable for use in potentially explosive atmospheres in accordance with the directive 2014/34/EU, as well as the IECEx scheme.

It is approved as an accessory device. Ex-marking see type examination certificate of the corresponding device. Compatible devices can be found at [www.isafe-mobile.com](http://www.isafe-mobile.com).

## FEATURES

16 PIN socket | suitable for all 16 ISM interfaces

PTT (Push to Talk) key with build-in microphone, crystal clear sound

Transparent flexible acoustic tube

Soft earplug is comfortable even wear for a long time

Please visit our website and you will find more detailed information, as well as an overview of our devices.

# i.safe MOBILE

## GROUP I M1 MINING



1D or 2D  
Barcode up to 18 m  
scan distance

### IS-TH1xx.M1



The mobile multifunctional set consisting of a Trigger Handle (hand-held barcode scanner) and an industrial smartphone IS530.x is a flexible combination for reliable data acquisition in Ex areas. The HID-active, ready-to-use high-performance scanner captures any 1D or 2D barcodes at close range of up to 6 meters or distances of up to 18 meters via the reliable Zebra OEM imager scan engines. The data is further processed directly via the IS530.x smartphone connected via the ISM interface.

› All trademarks and copyrights are the properties of their respective owners. › © 2022 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1055MD01REV04\_EN\_02.2024



## IS-TH1xx.M1



ATEX approval: Mining  
I M1 Ex ia op is I Ma  
II 2G Ex ib op is IIC T4 Gb  
II 2D Ex ib op is IIC T135°C Db



IECEx approval: Mining  
Ex ia op is I Ma  
Ex ib op is IIC T4 Gb  
Ex ib op is IIC T135°C Db

### TECHNICAL FEATURES

|                            |                                                                     |
|----------------------------|---------------------------------------------------------------------|
| <b>Weight</b>              | MR = 380 g   ER = 400 g (without IS530)                             |
| <b>Size</b>                | 202 x 90,4 x 125 mm                                                 |
| <b>Indication function</b> | Loudspeaker   Vibration   LED-Display                               |
| <b>Power supply</b>        | Over IS530   this can be loaded in the handle                       |
| <b>Communication</b>       | Over the multi functional ISM interface of the IS530                |
| <b>Type of protection</b>  | MIL-STD 810H   IP68 dust-/waterproof   usable from -20 °C to +60 °C |

### SCAN TYPES

- **IS-TH1MR.M1** (mid range) with **Zebra SE4750 MR** | up to 6 m
- **IS-TH1ER.M1** (extended range) with **Zebra SE4850 ER** | up to 18 m



## IS530.M1



Android™ 13



4,5" Gorilla Glass®  
3. generation,  
resolution 854 x 480 pixels



3600 mAh battery,  
replaceable,  
3,8 V, 13,68 Wh



Bluetooth® 5



GSM 850/900/1800/  
1900 MHz  
WCDMA: UMTS B1/2/4/5/8/  
LTE-FDD: B1/2/3/4/5/7/8/12  
with MFBI B13/14/17/20/25/  
26/28A/28B/29/30/66  
LTE-TDD: B38/B39/B40/B41  
TD-SCDMA: B34/B39



Qualcomm Snapdragon  
SDM660 Octa-Core  
Kryo Gold-Quad cores  
2,2 GHz  
Kryo Silver-Quad cores  
1,8 GHz  
4 GB RAM  
64 GB internal memory



2,4 GHz + 5 GHz: IEEE  
802.11 a/b/g/n/ac/e/k/r/h  
with hotspot for max. 8  
connections

The complete description you will find on our homepage: [www.isafe-mobile.com](http://www.isafe-mobile.com)

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.

## GROUP I M1 MINING



13-pin ISM interface



Android™ 13

Zero-touch capable  
MDM compatible

IS530.M1



The powerful, particularly dust-proof industrial smartphone for the mining industry can be used in a variety of ways thanks to the ISM interface. Additional modules such as an RSM, PTT headsets or the professional barcode scanner IS-TH1.1 make the IS530.1 a high-performance multifunctional device. The smartphone is Android Enterprise Recommended, zero-touch capable and MDM compatible.



IS530.M1



ATEX approval: Mining  
Ex ia I Ma IP64



IECEx approval: Mining  
Ex ia I Ma IP64



ANZEX approval: Mining  
Ex ia I Ma  
-20 °C ≤ Ta ≤ +60 °C



EAC approval: Mining  
PB Ex ib I Mb X

Further approvals: SANS (South Africa)

### TECHNICAL FEATURES

|                            |                                                                                                                                                                                                   |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Operating system</b>    | Android™ 13                                                                                                                                                                                       |
| <b>Processor</b>           | SDM660 Octa-Core (Kryo Gold-Quad cores 2,2 GHz; Kryo Silver-Quad cores 1,8 GHz)                                                                                                                   |
| <b>Memory</b>              | 4 GB RAM   64 GB internal memory   microSD memory up to 128 GB                                                                                                                                    |
| <b>Frequencies</b>         | 2G GSM: 850/900/1800/1900 MHz<br>3G WCDMA: UMTS B1/2/4/5/8<br>4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFB1 B13/14/17/20/25/26/28A/28B/29/30/66<br>4G LTE-TDD: B38/B39/B40/B41<br>4G LTE-SCDMA: B34/B39 |
| <b>Dimensions</b>          | size: 155 x 80 x 25 mm   weight: 325 g                                                                                                                                                            |
| <b>Display</b>             | 4,5" Gorilla Glass® 3. generation   854 x 480 pixels   usable with gloves                                                                                                                         |
| <b>Battery</b>             | 3600 mAh, 3,8 V, 13,68 Wh   replaceable                                                                                                                                                           |
| <b>Camera</b>              | 13 MP AF rear camera   5 MP FF front camera                                                                                                                                                       |
| <b>Connections</b>         | WiFi 2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot<br>Bluetooth® 5<br>GPS, A-GPS, Glonass, Beidou, Galileo<br>Near Field Communication                          |
| <b>Types of protection</b> | IP68 dust-/waterproof   MIL-STD-810G   usable from -20 °C to +60 °C                                                                                                                               |

### FURTHER FEATURES



SOS key for loneworker protection  
LWP ready (third party application required,  
based on country specific regulations)



13-pin ISM interface for a quick and safe  
connection of additional devices for a  
wide range of applications



Dual micro-SIM



Amplified loudspeaker



Magnetic charger port



Accelerometer, gyroscope, light, magnetic,  
proximity, pressure sensors

### SET CONTENT

Smartphone, Battery, i.safe PROTECTOR 2.0 Type C USB Cable, i.safe PROTECTOR 3.0 USB Magnetic Charger Cable, Power Adapter universal, Screwdriver, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.

SIM card -  
easy to install



## GROUP I M1 MINING



- › Very high level of safety in the mining sector with the risk of firedamp
- › Zero-touch capable
- › Android™ 13

IS930.M1



The robust, powerful and particularly dust-proof tablet of the Industry 4.0 generation is ideal for use in the mining industry. The Android Enterprise Recommended device can be used immediately thanks to its zero-touch functionality and is ideally suited for maintenance applications in the IoT environment. The 8-inch display, two freely programmable buttons, a long-life battery, a practical hand strap, leather bag with a shoulder/belt or carry strap system are further highlights.

› Android is a trademark of Google LLC. All trademarks and copyrights are the properties of their respective owners. › © 2023 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1030MD03REV10\_EN\_03.2024



< IS930.M1 >



ATEX approval: Mining  
Ex ia I Ma IP64



IECEx approval: Mining  
Ex ia I Ma IP64



ANZEx approval: Mining  
Ex ia I Ma  
-20 °C ≤ Ta ≤ +60 °C



EAC approval: Mining  
PB Ex ib I Mb X

Further approvals: SANS (South Africa)

## TECHNICAL FEATURES

|                            |                                                                                                                                                                                                   |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Operating system</b>    | Android™ 13                                                                                                                                                                                       |
| <b>Processor</b>           | SDM660 Octa-Core (Kryo Gold-Quad cores 2,2 GHz; Kryo Silver-Quad cores 1,8 GHz)                                                                                                                   |
| <b>Memory</b>              | 4 GB RAM   64 GB internal memory   microSD memory up to 512 GB                                                                                                                                    |
| <b>Frequencies</b>         | 2G GSM: 850/900/1800/1900 MHz<br>3G WCDMA: UMTS B1/2/4/5/8<br>4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/26/28A/28B/29/30/66<br>4G LTE-TDD: B38/B39/B40/B41<br>4G LTE-SCDMA: B34/B39 |
| <b>Dimensions</b>          | size: 237 x 156 x 22 mm   weight: 890 g                                                                                                                                                           |
| <b>Display</b>             | 8" Gorilla Glass® 3. generation   1200 x 1920 pixels                                                                                                                                              |
| <b>Battery</b>             | 8400 mAh                                                                                                                                                                                          |
| <b>Camera</b>              | 13 MP AF rear camera   5 MP FF front camera                                                                                                                                                       |
| <b>Connections</b>         | WiFi 2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot<br>Bluetooth® 5<br>GPS, A-GPS, Glonass, Beidou, Galileo<br>Near Field Communication                          |
| <b>Types of protection</b> | IP68 dust-/waterproof   MIL-STD-810H   usable from -20 °C to +60 °C                                                                                                                               |

## FURTHER FEATURES



SOS key for loneworker protection  
LWP ready (third party application required,  
based on country specific regulations)



2 freely programmable keys



Usable with gloves



Accelerometer, gyroscope, magnetic,  
temperature and humidity, proximity sensors



Magnetic charger port

## SET CONTENT

Tablet with integrated battery, Hand Strap, i.safe PROTECTOR 2.0 Type C USB Cable, i.safe PROTECTOR 3.0 USB Magnetic Charger Cable, Power Adapter universal, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.